



H320P -- Straight Blade Products, IEC H320 Series



Straight Blade Devices, IEC 320 Devices, Male Plug, 16A 250V, International Rated, Pressure Screw Terminal, Black, Single Pack

Product Specifications

| | |
|--------------------------------|--|
| Product Type |  <p>IEC320 Devices</p> |
| IEC Product | Plug |
| Standard | IEC 320 |
| Amperage | 20A/16A |
| Voltage | 250V |
| Poles and Wires | 2-pole + earth. |
| Wiring Method | Terminal Screw |
| Color |  <p>Black</p> |
| Cord Dia. | .325"-.475" (8-12) |
| Rating | 16A 250V AC for European service; 20A 250V AC for North American service. |
| Certification | UL Listed 20A 250V AC-File No. E1706; CSA certified 20A 250V AC-File No. 17337; UL classified to IEC 320, 16A 250V AC-File No. E111246; TUV and VDE certified at 16A 250V AC-File No. 12469 1550 1002. |
| IP Suitability | IP20 |
| Housing Material | Nylon-Black |
| Retainer Material | Nylon-Black |
| Cord Clamp Material | Nylon-Black |
| Contact Blades Material | .040" (1.0) Brass |
| Terminal Screw Material | Steel |
| Ground Screw Material | Steel |
| Base Material | Nylon |
| Power Contacts Material | .032" (.81) Brass |
| Dielectric Voltage | Withstands 2,000V minimum. |
| Current Interrupting | Certified for current interrupting at full rated current. |
| Temperature Rise | Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%.. |
| Terminal Identification | Terminals identified in accordance with UL498 (Brass, White, Green). |
| Terminal Accommodation | #16-#12 AWG copper stranded or solid conductor only. |
| Product Identification | Ratings are a permanent part of the device. |
| Flammability | UL 94 HB or better. |
| Operating Temperatures | Maximum continuous 75°C, minimum -40°C (w/o impact). |
| M Drawings | Click here for M-Drawing |

| | |
|------------------------|---|
| Catalog Page | Click here for catalog page A34 |
| Catalog Section | Click here for Section-A |
| UPC Number | 783585777061 |
| Weight in LBs | 0.150 |

